IP65 Plastic Units Datasheet
CU03 & CU05 and Populated Versions

Model shown: CU03

Model shown: CU05/2A

CONSTRUCTION AND FEATURES:

- Transparent cover
- 3 unit size variants:
  - ♦CU03—3 ways
  - ♦CU05—5 ways
- Keyhole mounting points
- Pre-fitted earth and neutral terminal bars
- Neutral cable and accessory pack included (busbar, grommets, plastic blanks and labels)
- DIN rail included
- Hinged cover with catch and gasket
- Fast release cover fixings
- Populated versions available
- Other populated versions built on request

TECHNICAL DATA:

- IP65 rated
- Flame retardant plastic
- Earth contact points for added safety
- Various sized knockouts up to 35mm
- RCD's: Type A 63A, 30mA, BS EN 61008 compliant
- MCB's: BS EN 60898-1 compliant

Note: Type AC RCDs can only be used on a fixed load system, with NO DC elements

Populated variants:

Shower units

- CU03/1A: 1x 63A - 30mA - Type A RCD, 1x 40A - MC - C curve - MCB
- CU03/2A: 1x 63A - 30mA - Type A RCD, 1x 50A - MC- C curve - MCB

Garage units

- CU05/1A: 1x 63A - 30mA - Type A RCD, 1x6A & 1x20A - MD - B curve - MCB
- CU05/2A: 1x 63A - 30mA - Type A RCD, 1x6A & 1x16A - MD - B curve - MCB
- CU05/5A: 1x 63A - 30mA - Type A RCD, 1x6A & 1x32A - MD - B curve - MCB

Unit Dimensions:

	HEIGHT	WIDTH	DEPTH
CU03	184mm	100mm	110mm
CU05	184mm	136mm	110mm

Cudis Ltd | Unit 7 | Bridge Trading Estate | Bolton Road | Bury | Lancashire | BL8 2AQ

0161 989 5636
sales@cudis.co.uk
www.cudis.co.uk

Company Number: 5230706
VAT Number: 286 3362 60

INFORMATION SUBJECT TO CHANGE WITHOUT NOTICE, SEE CUDIS TERMS AND CONDITIONS,FOR ADDITIONAL INFORMATION REFER TO THE APPLICABLE STANDARD